

Features



- ▶ LED Backlight Unit
- ▶ Most Advanced Panel
- ▶ Multi Language OSD Support
- ▶ Connectivity – RGB , DVI , HDMI(Optional)
- ▶ Touch Screen / Tempered Glass (Option)
- ▶ High Brightness / Optical Bonding (Option)
- ▶ VESA Mount

Model		IGO056ND	IGO080ND	IGO097ND	IGO104ND
Display	Screen Size(Inch/BLU)	5.6 , LED	8.0, LED	9.7 , LED	10.4 , LED
	Resolution	640 x 480	800 x 600	1024 x 768	800 x 600
	Active Area (mm)	112.896 x 84.672	162.0 x 121.5	196.608 x 147.456	211.2 x 158.4
	Pixel Pitch (mm)	0.0588 x 0.1764 mm	0.0675 x 0.2025	0.192x 0.192	0.088 x 0.264
	Brightness (cd/m ²)	200	250	350	250
	Contrast Ratio	500 : 1	500 : 1	800 : 1	500 : 1
	Aspect Ratio	4 : 3	4 : 3	4 : 3	4 : 3
	Display Color	16.2M	16.2M	16.7M	16.2M
	Response Time (ms)	10	25	25	20
	Viewing Angle (degree)	140 / 120	140 / 120	178 / 178	140 / 110
	Lamp Life Time (Hours)	20,000	20,000	Up to10,000	10,000
Interface	VGA In (15Pin D-Sub)	1	1	1	1
	DVI In	1	1	1	1
	HDMI In	Optional	Optional	Optional	Optional
Audio	PC Stereo In	Optional	Optional	Optional	Optional
	Built in Speakers	Optional	Optional	Optional	Optional
Special Features	Touch Screen	Optional	Optional	Optional	Optional
	Tempered Glass	Optional	Optional	Optional	Optional
	High Brightness	Optional	Optional	Optional	Optional
	Transflective	Optional	Optional	Optional	Optional
	Optical Bonding	Optional	Optional	Optional	Optional
	Light Control	Optional	Optional	Optional	Optional
	Temp. Control	Optional	Optional	Optional	Optional
Cabinet	Multi Lingual Language	English, Spanish, French, German, Italian			
	Material	Metal / GI	Metal / GI	Metal / GI	Metal / GI
Power	Consumption : < On	<7W	<8W	<10W	<13W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)	AC100 ~ 240V(50/60Hz)
Circum-stance	Operating Temperature	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C	0 ~ 50°C
	Storage Temperature	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C	-20 ~ 60°C
Mounts	VESA Mounts Size (mm)	75 x 75	100 x 100	100 x 100	100 x 100